

CH21 Series

Total Lock Brake Stem Hospital Casters
Capacity to 260 lbs

Our CH21 Series Total Lock Brake Stem Hospital Casters are designed for use on crash carts, case carts, and other hospital and medical equipment. This series features double ball race swivel sections, a variety of mounting options, and optional direction locks and total lock brakes. All wheels in this series feature integral precision ball bearings and thread guards.

An antimicrobial treated thermoplastic wheel is available.



Series Specifications

Capacity	up to 260 lbs
Wheel Size	3", 4", 5", 6" diameter x 1-1/4" tread width
Bearings	Precision Ball (B), Delrin (D), Plain (P)

Options

Option Code	Description
DL	Direction Lock
TLB	Total Lock Brake
SS	Stainless Steel (Change CH to SS)

Building a Caster Part Number

To build your caster part number, use the base part number marked in the data block and add S for Swivel, there are no rigid casters in this series, then add a stem code from the stems or expanding adaptaters above. Append the part number with a brake, if desired.



CH21 Series

Total Lock Brake Stem Hospital Casters
Capacity to 260 lbs

Wheel Options

TR Thermoplastic Rubber

Standard Bearing: Precision Ball (B)



Quiet and smooth rolling, thermoplastic rubber wheels are floor protective and easy to start. Flat tread adds capacity.

3"x1¼"

Cap: 190 lbs
OAH: 4-7/16"
PN: CH21TRB30S

4"x1¼"

Cap: 240 lbs
OAH: 5-7/16"
PN: CH21TRB40S

5"x1¼"

Cap: 260 lbs
OAH: 6-7/16"
PN: CH21TRB50S

6"x1¼"

Cap: 260 lbs
OAH: 7-13/32"
PN: CH21TRB60S

PP Polyurethane on Plastic

Standard Bearing: Precision Ball (B)



Durable and easy to roll, polyurethane wheels are excellent for indoor or outdoor applications.

3"x1¼"

Cap: 190 lbs
OAH: 4-7/16"
PN: CH21PPB30S

4"x1¼"

Cap: 240 lbs
OAH: 5-7/16"
PN: CH21PPB40S

5"x1¼"

Cap: 260 lbs
OAH: 6-7/16"
PN: CH21PPB50S

6"x1¼"

Cap: 260 lbs
OAH: 7-13/32"
PN: CH21PPB60S

AM Antimicrobial Thermoplastic Rubber

Standard Bearing: Precision Ball (B)



These wheels are quiet, smooth rolling, and prevent the spread of bacteria and other microbial organisms throughout your facility.

3"x1¼"

Cap: 190 lbs
OAH: 4-7/16"
PN: CH21AMB30S

4"x1¼"

Cap: 240 lbs
OAH: 5-7/16"
PN: CH21AMB40S

5"x1¼"

Cap: 260 lbs
OAH: 6-7/16"
PN: CH21AMB50S

6"x1¼"

Cap: 260 lbs
OAH: 7-13/32"
PN: CH21AMB60S

Stem Mounting Options

G Grip Ring Stem

Append stem code to part number



Commonly found on chairs, rotationally molded plastic furniture, and some extruded metal products.

G723

Diameter: 7/16"
Length: 1-7/16"
Stem: -G732

T Threaded Stem

Append stem code to part number



Normally found on formed and welded metal furniture. Occasionally found on wood furniture and attached with a t-nut.

T824

Thread: 1/2-13
Length: 1-1/2"
Stem: -T824